



This is the regulator of choice for any demanding divers that dive with air or trimix with a maximum of 21% oxygen. Outstanding performance and certified to 200 meters!

Trimix and air  
5 LP and 2 HP-ports  
Low WOB - Servo assisted  
Certified to 200 m  
Delivered with a 70 cm hose

## PURE FACTS

<b>Approved to depth (m/f)</b>	<b>200/656 (gas dep.)</b>
<b>IP(bar/psi):</b>	<b>8,5 / 123</b>
<b>Air:</b>	<b>Yes</b>
<b>Trimix:</b>	<b>Yes (max 21% oxygen)</b>
<b>Nitrox 50%</b>	<b>No</b>
<b>Oxygen (99,95%):</b>	<b>No</b>
<b>Working pressure 300bar:</b>	<b>Yes</b>
<b>Built in anti freeze prot.:</b>	<b>Yes</b>
<b>O-rings:</b>	<b>Nitril/EPDM</b>
<b>US Navy tested:</b>	<b>Yes</b>
<b>Oxygen Approved (EN738-1):</b>	<b>Nej</b>
<b>NORSOK approved:</b>	<b>Yes</b>
<b>EN250 approved (cold water):</b>	<b>Yes</b>
<b>CE Cold water approved:</b>	<b>Yes</b>

### 2nd stage Xstream Deep Mk3

<b>Color</b>	<b>Black</b>
<b>Material</b>	<b>ASA/TPU Stainless steel Brass</b>
<b>Weight (g/lb)</b>	<b>152/0.33</b>
<b>Volume (ml/cuin)</b>	<b>49,5/3.0</b>
<b>Valve technology</b>	<b>Upstream</b>
<b>Flowrate (l/cuft per min)</b>	<b>2150/76</b>
<b>Oxygen cleaned</b>	<b>No</b>
<b>Servo assisted valve</b>	<b>Yes</b>
<b>Overpressure valve built in to the LP hose</b>	<b>No</b>
<b>Dismountable w/o tools</b>	<b>Yes</b>
<b>Push button on side</b>	<b>Yes</b>
<b>Swiveling</b>	<b>Yes</b>
<b>Non keyed (no up or down)</b>	<b>Yes</b>

### Xstream Deep first stage

<b>Color:</b>	<b>Black</b>
<b>Technology:</b>	<b>Roll diaphragm</b>
<b>Material:</b>	<b>Brass</b>
<b>Valve technology:</b>	<b>Spheric</b>
<b>Wheel mounted:</b>	<b>Side</b>
<b>LP ports 3/8:</b>	<b>5</b>
<b>HP port 7/16:</b>	<b>2</b>
<b>Flow rate (l/min):</b>	<b>5500</b>
<b>O2 clean:</b>	<b>No</b>
<b>DIN G5/8:</b>	<b>Yes</b>
<b>EN144-3 compatible:</b>	<b>No</b>
<b>Separate yoke:</b>	<b>Accessory</b>
<b>Zytel HP seat:</b>	<b>Yes</b>
<b>Built in overpressure valve:</b>	<b>Yes</b>
<b>Anti-freeze protected:</b>	<b>Yes</b>